

TR28 QUOTATION SHEET

TO:	
PLACE OF DELIVERY:	Qingdao Port
WARRANTY:	1 Year(since the date that buyer receive the machine)
PACKING WAY:	2 Units In 40HQ container
TERMS OF PAYMENT:	
DELIVERY TIME	20-25 days days after deposit.
Minimum Order	1 Unit

MODEL	DESCRIPTION	U-P (FOB QINGDAO)	QTY	AMOUNT
TR28	Standard Bucket, Quick Hitch , Hydraulic Torque Converter Transmission, DEUTZ WP6G125E2 Engine(92KW), Luxury Cabin, Hydraulic Joystick , Hydraulic Pressure Checking System, Adjustable Steering Wheel, Comfortable Seat, Luxury Cabin Interiors, 17.5-25 Tyres, Heater, Backward Camera ,		1	
OPTIONS				
TOTAL FOB QINGDAO				

Picture I



Picture II



Optional Equipments:

Electric Joystick		Loader Damper	
E4 Lamp		Loading Weighter	
LED Working Light		Centralization Lubrication	
LED Alarm Light		Bobcat Quick Hitch	
Extra Hydraulic Line		Euro Quick Hitch	
Trailer Ball		Trima Quick Hitch	
Multi-functions Electric Joystick with 5 buttons		Extra Heater	
Multi-functions Electric with 4 buttons		Extra Oil Cooler	
Rear Hydraulic Line		8 Gears Shift	
Extra Electric Line		Air Seat(without Air Pump)	
Rear Sand Spreader Oil Line + Left Joystick		Crane Valve	
3 Point Hitch		Diesel Heater	
Air Conditioner		Tyre Chains	
Varta Anti-Freeze Battery			

Optional Tires & Engines:

16/70-24 Tires			
----------------	--	--	--

Attachments:

Pallet Forks		V-Snow Blade	
Adjustable Pallet Forks		Snow Blade With Wings	
Grapple Forks		Crops Blade	
European Grapple Forks		Bale Grab	
Wooden Forks		Drum Folder	
360 Degree Wooden Forks		Sweeper	
Manure Forks		Sweeper With Collector	
Grapple Bucket		Sweeper With Water Tank	
4 In 1 Bucket		Auger(400Mm)	
Light Bucket		Hammer	
Snow Bucket		Flail Mower	
Snow Bucket With Wings		Cutter Head	
Mixer Bucket		Snow Blower	
Rock Bucket		Digger	

Crops Bucket(1.6m3)		Digger With Thumb	
High-Dumping Bucket		Hydraulic JIB	
Tilting Bucket		JIB	
Sand Spreader(Front)		Rake	
Salt Spreader		Hay Forks(One Fork)	
Sand Spreader(Rear)		Hay Forks(Two Forks)	
Snow Blade		Double-Blade Bucket(1.5m3)	

Specifications:

Item	specifications
Overall working weight	7000kg
Rated bucket capacity	0.72m ³
Rated load	2800kg
Max. tractive force	65KN
Max. breakout force	≥65KN
Max. gradeability	30°
Max. dumping height	3500mm
Dumping distance	950mm
Overall dimension (L×W×H)	6470×2120×2960mm
Engine	
Model	Weichai WP6G160E20
Type	Inline, water cooling, dry cylinder, direct injection
Number of cylinder-bore/stroke	6-108×125mm
Rated power	92kw
Rated speed	2200r/min
Mini fuel-consume ratio	≤210g/kw.h
Transmission system	
Torque converter	Single-stage
Torque ratio	3.2
Transmission type	Planetary power shift
Gear shift	2 forwardshift, 2 reverseshift
Max. speed	21km/h
Front and rear axles	
Main transmission type	Spiral gear, first stage decelerate
Final decelerate type	First stage, planetary gear decelerate

Tyre

Tyre specification	17.5-25
Front tyre pressure	275KPa
Rear tyre pressure	275KPa

Steering system

Type	Articulated load-sensing hydraulic steering system
Steering angle	±35
Mini turning radius	5200mm
system working pressure	16MPa
Boom lifting time	6s
Total time	11s

Brake system

Service brake	Air-on-oil, caliper-disk
parking brake	Manual caliper disc

Capacity

Fuel	80L
Hydraulic	80L

