

TR35 QUOTATION SHEET

TO:

PLACE OF DELIVERY: Qingdao Port

WARRANTY: 1 Year(since the date that buyer receive the machine)

PACKING WAY: 1 unit In 40HQ container

TERMS OF PAYMENT:

DELIVERY TIME 20-25 days days after deposit.

MODEL	DESCRIPTION	U-P	QTY	AMOUNT
TR35	Standard Bucket, Luxury Cabin, Weichai DEUTZ-92KW Engine, Comfortable Seat, Hydraulic joystick, Electrical Gear Shift, Heater, Lock for Lifting and Steering Cylinder, Backward Imagine, Automatic Gear Box,		1	
Picture I		Picture II		



Optional Equipments:

Quick hitch		3 Point Hitch	
E4 Lamp		Air Conditioner	
LED Working Light		Varta Anti-Freeze Battery	
LED Alarm Light		Loader Damper	
Extra Hydraulic Line		Loading Weighter	
Trailer Ball		Centralization Lubrication	
Multi-functions Electric Joystick with 5 buttons		Euro Quick Hitch	

Multi-functions Electric with 4 buttons		Trima Quick Hitch	
Extra Electric Line		Air Seat(without Air Pump)	
Rear Sand Spreader Oil Line + Left Joystick			

Optional Tires & Engines:

20.5-25 Tires		DF Cummins Engine	
Cummins 6BT5.9 Engine(Euro3)		Kohler3403 Tier4 Engine	

Attachments:

Pallet Forks		3.6M Rake	
Rock Bucket		Double-Blade Bucket(2m3)	
Snow Blower		4 in 1 bucket	
Snow bucket with wings		Rear sand spreader	
Rear Rake		Slashers	
Hay forks		Standard Bucket	
HD Slashers		4 in 1 bucket(2m3)	
Pallet Forks		Rake	
Rock Bucket		Double-Blade Bucket(2m3)	
Snow Blower		4 in 1 bucket	
Snow bucket with wings		Rear sand spreader	
Slasher			

Specifications:

1.0 Engine Details

(1) Model:	DEUTZ WP6G125E23
(2) Engine Type:	In-line arrangement,water-cooled,four-cycle diesel engine
(3) Rated Power:	92 KW
(4) Rated Speed:	2000 r/min(rpm)
(5) Fuel Consumption ration in Standard working condition:	≤227g/kw.h

2.0 Transmission System

(1) Type:	Single state,3 elements
(2) Torque ration:	3.25
(3) Transmission Type:	Shaft power shift

(4) Number of gear:	3 forward shift,2 reverse shift
(5) Max speed:	40km/h
3.0 Bucket	
(1) Bucket capacity:	1.8 m3
(2) Bucket type:	Heavy-duty bolt on teeth
(3) Max. Breakout Force:	≥96KN
(4) Max Traction Force:	≥96KN
(5) Rated Load:	3000kg
(6) Operating Weight:	12000kg
4.0 Overall Dimensions	
(1) Overall Length :	6970/7185mm
(2) Overall Height:	3087mm
(3) Overall width:	2510mm
5.0 Operating Specifications	
(1) Steering system:	Articulated frame with hydraulic power steering
(2) Min.turning radius:	5882/5349mm
(3) Driving system:	Hydraulic converter
(4) Max.Climbing Ability:	30°
(5)Max Dumping Reach:	2950mm
(6)Dumping Distance:	1050mm
6.0 Brake System	
(1) Service Brake	Four wheel hydraulic spread-shoed brake
(2) Parking Brake	Hand operated
7.0 Tyre	
(1) Model:	17.5-25 Tyre
(2)Front Tyre Pressure:	0.333-0.353MPa
(3)Rear Tyre Pressure:	0.275-0.294MPa
8.0 Front and Rear Axles	
(1)Main Transmission Type:	Spiral Gear,First Stage Decelerate
(2)Final Transmission Type:	First Stage,planetary Gear Decelerate
9.0 Fill Capacity:	
(1)Fuel:	140L
(2)Hydraulic Oil:	130L

